

ANTIDARK

EASY W100 datasheet



EASY W100

8.9W LED. Dimmable. 230V. 2700K. 726lm. 64 lm/W.
BA32°. CRI90+. 50.000h. IP20. 360° Vertical | 90°
Horizontal Ø:10cm. H: 10.5cm. Aluminium base | PVC
screen. 5 year warranty.

8,9W LED. Dæmpbar. 230V. 2700K. 726lm. 64 lm/W.
BA32°. CRI90+. 50.000h. IP20. 360° Vertikal | 90°
Horizontal. Ø:10cm. H: 10.5cm. Aluminiums base | PVC
skærm. 5 års garanti.

2-215-05-1
White/ hvid

EAN 5706872018109

2-215-05-2
Black/ sort

EAN 5706872018116

EASY W100 Wirehole

8.9W LED. Dimmable. 230V. 2700K. 726lm. 64 lm/W.
BA32°. CRI90+. 50.000h. IP20. 360° Vertical | 90°
Horizontal. Ø:10cm. H: 10.5cm. Aluminium base | PVC
screen. With wire hole cutout. 5 year warranty.

8,9W LED. Dæmpbar. 230V. 2700K. 726lm. 64 lm/W.
BA32°. CRI90+. 50.000h. IP20. 360° Vertikal | 90°
Horizontal. Ø:10cm. H: 10.5cm. Aluminiums base | PVC
skærm. Med ledningshul. 5 års garanti.

2-215-05-10
White/ hvid

EAN 5706872019557

2-215-05-20
Black/ sort

EAN 5706872019526