WEVER & DUCRÉ LIGHTING

PIRRO SPOT on track 2.0

173264K5

PROJECT

TYPE


NOTES

QUANTITY

DATE



Spotlight made from die-cast aluminium incl. 1-phase track adapter; with 2 spotlights; opal PMMA cover; housing Black Matt powder coated; matt texture; with reflector in Gold wet painted; matt smooth; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 32°; 310° rotatable; degree of protection IP20; Class 1; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



GENERAL

Ceiling
Track
rotation 310 °
Black Matt + Gold
IP20
Interior
770 lm
CIE flux code: 99 100 100 100 100

LED

3000 K
CRI ≥ 90
L70 / 55000h
initial MacAdam ≤ 2 SDCM

OPTICAL

Standard
beam angle 32°


ELECTRICAL

phase-cut dim
220 - 240 V
system 11.0 W
Class 1

PHYSICAL

length 94 mm
width 50 mm
height 80 mm
0.36 kg
adapter 75 mm
incl. 1-phase track adapter

LIGHT DISTRIBUTION



['173264K5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

PIRRO SPOT on track 2.0

173264K5

CONE DIAGRAM

standard 31°

h (m)	E0° (lx)	ø (m)
1	2210	0.55
2	550	1.11
3	250	1.66
4	140	2.22
5	90	2.77

MOUNTING ACCESSORIES

Adjustable Corner

Type	Colour	L·W·H (MM)	Item number
1-phase track	Black	81·81·20	90014041
1-phase track	White	81·81·20	90014042

X-Connector

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	145·145·20	90014049
1-phase track	Black	145·145·20	90014050

TRACK ACCESSORIES

Coverplate End Feed

Type	Colour	L·W (MM)	Item number
1-phase track | recessed	White	75·50	90014124
1-phase track | recessed	Black	75·50	90014125

Coverplate I/L/T/X

Type	Colour	L·W (MM)	Item number
1-phase track | recessed	White	100·100	90014126
1-phase track | recessed	Black	100·100	90014127

End Cap

Type	Colour	L·W·H (MM)	Item number
1-phase track | left/right	White	24·30·20	90014028
1-phase track | left/right	Black	24·30·20	90014029

End Feed | left

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	88·30·20	90014018
1-phase track	Black	88·30·20	90014019

End Feed | right

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	88·30·20	90014020
1-phase track	Black	88·30·20	90014021

['173264K5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

PIRRO SPOT on track 2.0

173264K5

L-Connector

Type	Colour	L·W·H (MM)	Item number
1-phase track | left	White	88·55·20	90014024
1-phase track | left	Black	88·55·20	90014025
1-phase track | right	White	88·55·20	90014026
1-phase track | right	Black	88·55·20	90014027

Middle Feed

Type	Colour	L·W·H (MM)	Item number
1-phase track | straight	White	145·30·20	90014036
1-phase track | straight	Black	145·30·20	90014037

Mounting Bracket

Type	L·W·H (MM)	Item number
1-phase track | recessed	35·59·35	90014100

Straight Connector

Type	Colour	L·H (MM)	Item number
1-phase track | straight	White	65·17	90014022
1-phase track | straight	Black	65·17	90014023

Suspension Set 1.5m

Type	Colour	Ø·H (MM)	Item number
1-phase track | suspended	White	29·1500	90014101
1-phase track | suspended	Black	29·1500	90014102

Suspension Set 3.0m

Type	Colour	Ø·H (MM)	Item number
1-phase track | suspended	White	29·3000	90014103
1-phase track | suspended	Black	29·3000	90014104

T-Connector 1.0

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	145·55·20	90014010
1-phase track	Black	145·55·20	90014011

T-Connector 2.0

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	145·55·20	90014012
1-phase track	Black	145·55·20	90014013

T-Connector 3.0

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	145·55·20	90014014
1-phase track	Black	145·55·20	90014015

T-Connector 4.0

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	145·55·20	90014016
1-phase track	Black	145·55·20	90014017

['173264K5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

PIRRO SPOT on track 2.0

173264K5

Track Adapter 1.0

Type	Colour	L·H (MM)	Item number
1-phase track	Black	85·45	90014043
1-phase track	White	85·45	90014044

TRACKS

Track Profile 1m

Type	Colour	L·W·H (MM)	Item number
1-phase track | surface/suspended	White	1000·30·20	90014001
1-phase track | surface/suspended	Black	1000·30·20	90014007
1-phase track | recessed	White	1000·50·20	90014118
1-phase track | recessed	Black	1000·50·20	90014119

Track Profile 2m

Type	Colour	L·W·H (MM)	Item number
1-phase track | surface/suspended	White	2000·30·20	90014002
1-phase track | surface/suspended	Black	2000·30·20	90014008
1-phase track | recessed	White	2000·50·20	90014120
1-phase track | recessed	Black	2000·50·20	90014121

Track Profile 3m

Type	Colour	L·W·H (MM)	Item number
1-phase track | surface/suspended	White	3000·30·20	90014003
1-phase track | surface/suspended	Black	3000·30·20	90014009
1-phase track | recessed	White	3000·50·20	90014122
1-phase track | recessed	Black	3000·50·20	90014123

['173264K5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com