



PROJECT

TYPE

NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; surface White Aluminium; wet painted, matt smooth; RAL 9006; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 120 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 2; lamp not included;

GENERAL

Ceiling
Recessed
White Aluminium
RAL 9006 ^a
IP20
Interior
CIE flux code: 94 98 100 100 93

LED

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

ELECTRICAL

100 - 240 V
Class 2

PHYSICAL

diameter 84 mm
height 112 mm
0.15 kg
wire springs

CUTOUT

diameter 76-79 mm
min. ceiling thickness 4 mm
max. ceiling thickness 38 mm
recessed depth 120 mm



^a Colour may deviate slightly due to production conditions.

MEASURED LAMPS

PAR16 LAMP 3000K CRI90
510 lm
6.5 W

PAR16 LAMP 2700K CRI90
470 lm
6.5 W

LIGHT DISTRIBUTION



**ELECTRICAL ACCESSORIES****LED LAMPS**

Colour	Item number
Black Texture	W901228B3
Black Texture	W901228B5

LAMPS**PAR16 LED Lamp**

Type	Colour	Ø·H (MM)	Item number
2700K >90 CRI GU10	White	50·60	901228W3
3000K >90 CRI GU10	White	50·60	901228W5
2700K >80 CRI GU10	Silver	50·60	905227S2
3000K >80 CRI GU10	Silver	50·60	905227S4