



Special features

- Power adjustable in four stages
- rotatable and swivelling
- low glare value

Housing Material	Aluminium	Product weight	583 g
Housing Color	White	Working Temperature	-25 to 45 °C
Material of Lens	Polycarbonate - PC	Storage Temperature	-25 to 50 °C
Functions	Phase switch	IP Protection Class	IP 20
Protection Class	Protection class II/protective insulation	Life Time L70 / B50	30000 h
Power Selectable	23 W, 28 W, 30 W, 32 W	Life Time L80 / B10	50000 h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Switching Cycles	15000
Rated Current Selectable	800 mA, 750 mA, 700 mA, 600 mA	Power Consumption	32 kWh/1000h
Power Supply Unit incl.	Yes	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Lightcolor	Warm white (WW)		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
CRI (Ra)	80		
Rated Luminous Flux	3010 lm		
Luminous Efficiency	91.6 lm/W		
Rated Angle of Reflection	36 Degree		
UGR	16		
Light Distribution	Symmetric		
Swivel Angle	25 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	336 mm		
Width	49 mm		
Height	98 mm		

