



PRO OFFICE SANO series ceiling lights are an efficient solution for renovating and modernising old T5/T8 louver lights. Due to slightly larger dimensions, the lights cover the old installations and so do not require the ceiling to be repainted.

Arrestor cables, plug connectors and mounting brackets make installation so easy that it can be performed by one person. In addition to ease of installation, the series offers impressive technical highlights: It provides flexible light control via CCT switch (3,000 K / 3,500 K / 4,000 K), dimmable variants (leading-edge/trailing-edge or DALI) and output adjustment in four stages (TRIAC variants only). They are also eligible for

**Special features**

- Renovation solution for T5/T8 louver lights
- Uniform illumination
- Covers the old installation, therefore no repainting necessary
- Easy to install due to plug connector, arrestor cables and mounting bracket
- Light colour adjustable in three levels
- Output adjustable in four levels [TRIAC variants only]
- Microprismatic surface structure
- Eligible for BEG German federal funding for energy-efficient build-

<b>Housing Material</b>	Aluminium, Stainless steel
<b>Housing Color</b>	White
<b>Functions</b>	Emergency power capable
<b>Protection Class</b>	Protection class I/protective grounding
<b>Power Selectable</b>	27 W, 30 W, 33 W, 35 W
<b>Rated Power Consumption Standby</b>	0.5 W
<b>Rated Input Voltage Frequency</b>	198-264 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Dimmable</b>	Yes
<b>Control</b>	Trailing-edge dimmer, Leading-edge dimmer
<b>Motion Detector</b>	No
<b>Voltage range emergency lighting</b>	176-280 V/DC
<b>EOFI</b>	95 %
<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000/3500/4000 K
<b>Colour Consistency</b>	3 SDCM
<b>Colour consistency light source</b>	3 SDCM
<b>CRI (Ra)</b>	90
<b>Rated Luminous Flux</b>	4200/4500/4400 lm
<b>Rated Angle of Reflection</b>	90 Degree
<b>UGR</b>	19
<b>Length</b>	625 mm
<b>Width</b>	625 mm
<b>Height</b>	48 mm
<b>Working Temperature</b>	-10 to 40 °C
<b>Storage Temperature</b>	-10 to 40 °C
<b>IP Protection Class</b>	IP 40
<b>Life Time L80 / B20</b>	50000 h

<b>Switching Cycles</b>	100000
<b>EEI</b>	E

